



# **UNDER COUNTER SOLID DOOR**

## Freezer KUF12-2-N / KUF12-2(HC) KUF12-2S-N / KUF12-2(600)(HC)





#### Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

#### Hydrocarbon(HC) refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low affect to global warming (ODP-0, GWP-3).

#### Side mount compressor unit

With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to be highly efficient in narrow spaces.

#### Exterior & interior of the cabinet

The Turbo Air K-series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. The K-series adds a touch of style to the most refined setting.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also thoroughly prevents the overflow of condensate water.

#### Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

Adjustable, heavy duty, PE (polyethylene) coated wire shelves

# Easy open front grille with condenser cleaning brush kit

Front grille cover is easily removable without any tools, which makes condenser cleaning easy and convenient at any time. Handy condenser cleaning brush is included inside the front grille cover.

### **Refrigerator holds 1°C ~ 8°C for the best in food** preservation



Available in 700mm as standard and slim 600mm deep



#### LED interior lighting & fan control (only at Turbo Air)

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

#### Standard features

- Anti-corrosion coated evaporator
- Self-contained system

Door locks standard

· Standard 125mm. swivel castors with locks on the front set

### **Optional features**

- 125mm castors fitted
- 180mm,105mm, 80mm castors optional
- Adjustable legs 100-155mm




# **UNDER COUNTER SOLID DOOR**


## Freezer KUF12-2-N / KUF12-2(HC) KUF12-2S-N / KUF12-2(600)(HC)

PLAN	VIE	N
------	-----	---


(unit : mm)











SIDE VIEW (Depth 700mm)

# AUSTRALIA BRANCH

### **TURBO AIR PTY LTD**

www.turboairinc.com.au 1st Floor, Building E 10 Highgate St, Auburn NSW 2144 Australia

#### Mode KUF12-2-N(HC KUF12-2S-N(600)(HC) Refrigerant R-290 R-290 COMP (HP) 1/3HP 1/3HP POWER INPUT(W) 400 400 3.75 3.77 **Energy consumption** AMPS(A) 2.5 2.5 234 Capacity 311 1200 Product Dimension W 1200 **Product Dimension D** 700 600 Min.Clearance height 860 Product Dimension H Min.Clearance height 860 Weight 84 71 SUS 439 SUS 439 Stainless steel Front Breathing Front Breathing Features Max GN Pan depth GN Pan Door lock yes yes Adjustable Shelves 2 2 LED light yes yes Temperature range -21°C~-12°C -21°C~-12°C 35°C 35℃ Ambient temperature Drainage / Heater + Soaking Paper Heater + Soaking Paper **Forced Evaporation** Temperature control **Digital control** Digital control Cooling type FAN COOLING FAN COOLING Glass Type

Design and specifications subject to change without notice. Actual Shipping w eight may differ due to extra packing materials for product protection.

DOOR LOCKS STANDARD

(Low-e / Heater How many layer of the glass)

- INTERIOR LED LIGHTING STANDARD
- Self-Contained System
- Standard 4" Swivel Casters with Locks **ON THE FRONT SET**
- ALUMINIUM DOOR FRAME
- Low-E DOUBLE GLASS
- DEPTH 600mm Available Upon Request







email: TA.admin@turboairinc.com.au

T. 02 9737 9881